



The Power of Innovation[®]

Female Splice Adapter CF81GHZ Series

PPC's CF81GHZC and CF81GHZM high performance "F" female splice adapters offer superior corrosion resistance and weather sealing capability.



Features

- Nickel-plated steel construction for superior corrosion protection
- Barrel designed to accept weather seals to prevent moisture migration (CF81GHZC Only)
- Compatible with WS500 weather seals (CF81GHZC Only)
- Gold plated center conductor contact

Specifications

		S.R.L.	I.L.
Bandwidth	0 MHz to 1 GHz	> 30dB	< .05 dB
	1 GHz to 2 GHz	> 30dB	< .05 dB
	2 GHz to 3 GHz	> 25dB	< .10 dB
Impedance	75 Ohms		
Operating Temperature	-40° to +140° F		

Tooling Requirements

- 7/16" wrench for installing drop fitting
- Pin Cutters

Part Numbers

	Application
CF81GHZC	3 GHz Indoor/Outdoor Splice
CF81GHZM	3 GHz Wall Plate Version
CF81GHZMHDW	3 GHz Includes Mounting Hardware



6176 East Molloy Road
East Syracuse, NY 13057-0278
Tel: 315-431-7200
Fax: 315-431-7201
E-mail: ppc@ppc-online.com
www.ppc-online.com